


- Plug-in unit
 - Fixed output voltages
 - Thermal fuse in transformer
 - Exchangeable DC plugs
 - Approvals:
 - Complies w. medical std EN 60601 (on request)
 - For updates: see www.mascot.no
- Plugg-inn enhet
 - Faste utgangsspenninger
 - Termosikring i transformator
 - Utskiftbare DC plugger
 - Godkjenninger:
 - Tilfredsst. medisinsk std EN 60601 (på forespørsel)
 - For oppdat.: se www.mascot.no



8510 not
 8610 8310
 only

Technical specifications		Tekniske data		8310	8510	8610	8710	8810	
Input voltage:	Inngangsspenning:	VAC	230 VAC +6/-10%, 50/60Hz						
Max. output power:	Maks. utgangseffekt:	VA	3,5	8,5	10,5	15	20		
Insulation class:	Isolasjonsklasse:		II						
Electrical safety standard:	Elektrisk sikkerhetsstandard:		EN 60742	EN 60742 EN 60950	EN 60742	EN 60065, EN 60742 EN 60950			
EMC standards	EMC standarder		EN 61000-6-3 EN 61000-6-1						
• Emission:	• Emisjon:								
• Immunity:	• Immunitet:								
Dimensions excl. plug:	Mål uten plugg:	LxWxH mm	75x45x49	95x51x57		100x51x63			
Weight:	Vekt:	g	220	390	390	450			

Voltage versions - Spenningsversjoner

VAC	Max. load (mA) / Maks. last (mA)				
	8310	8510	8610	8710	8810
3	1100	1500	2000	4000	
4,5	600	1000	1800	3200	
6	400	1300	1300	2300	3200
7,5	400	1300	1300	2300	3200
9	340	780	970	1600	2100
10,5	330			1400	1900
12		710	600	1100	1600
13	250				
15		510	640	1000	1300
16	220				
18	190	470	560	800	1100
21	160	340	340	700	950
24	140	310	380	500	850
28				490	700
35		140	260		
42	20			330	430

Individual data sheets are available at www.mascot.com / Individuelle dataark er tilgjengelige på www.mascot.com